

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Altra Rock Drill 150 CP
Synonyms: Rock Drill Oil
CAS Number: Blend

Company Identification

Allegheny Petroleum Products Co.
999 Airbrake Avenue
Wilmerding, PA 15148 USA
1-412-829-1990 (For product information)
1-800-424-9300 (For emergencies)
1-800-424-9300 or 1-703-527-3887 (CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

<u>Chemical Name</u>	<u>Amount</u>	<u>CAS Number</u>
PETROLEUM BASE OIL, SOLVENT-DEWAXED PARAFFINIC	< 90.0 %	64742-65-0
ALKANES, CHLORO, C14-C17	5.0 - 10.0 %	Proprietary
NON-HAZARDOUS ADDITIVES	< 5.0 %	Proprietary

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

COMPOSITION COMMENT:

This product does not contain any components required to be reported per the SARA Section 313.

HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

3. HAZARDS IDENTIFICATION

HMIS Rating - Health: 1
 Flammability: 1
 Reactivity: 0

POTENTIAL HEALTH EFFECTS

EYE:

May be slightly irritating.

SKIN:

Prolonged or repeated contact may cause skin irritation, local redness and swelling.

INHALATION:

High vapor concentrations are irritating to the eyes, nose, throat, and lungs.

INGESTION:

Small amounts (a tablespoonful) swallowed during normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury.

CHRONIC EFFECTS:

None reported.

CARCINOGENICITY INFORMATION:

None known.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:

Wash skin with plenty of soap and water while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

INHALATION FIRST AID:

Remove to fresh air.

If not breathing, give artificial respiration and contact a physician immediately.

(section 4 continued)

INGESTION FIRST AID:

For larger amounts, do NOT induce vomiting, but give one or two glasses of water to drink and get medical attention. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

COC Flash Point: > 176.7 C (> 350.1 F)
Autoignition Temperature: N/A

FLAMMABLE LIMITS IN AIR

LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:

Carbon dioxide, foam, or dry powder. Do not use water, because this product is oil based. Water may cause frothing.

FIRE & EXPLOSION HAZARDS:

Can burn in fire, releasing toxic vapors, fumes, and smoke.

FIRE FIGHTING INSTRUCTIONS:

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:

Hazardous decomposition products are oxides of carbon and nitrogen including CO and CO₂.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

INITIAL CONTAINMENT:

Absorb spills with inert material. Do not allow material to enter soil or surface water.

LARGE SPILLS PROCEDURE:

Absorb spill with inert material (e g, dry sand or earth), then place in a chemical waste container. Do not flush to sewer.

(section 6 continued)

SMALL SPILLS PROCEDURE:

Absorb spills with inert material.

MISCELLANEOUS:

Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Secure container after each use. Store in a cool dry area.

Avoid contact with strong oxidizing agents.

STORAGE PRECAUTIONS:

Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

EYE / FACE PROTECTION REQUIREMENTS:

When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

SKIN PROTECTION REQUIREMENTS:

Where contact is likely, wear chemical resistant gloves.

RESPIRATORY PROTECTION REQUIREMENTS:

Under normal use conditions, with adequate ventilation, no special handling equipment is required. If mists are produced, local ventilation may be required to keep exposure below limits.

(section 8 continued)

EXPOSURE GUIDELINES:

No Information Available.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Amber
ODOR: Petroleum
VAPOR DENSITY: Heavier than air (Air = 1)
SOLUBILITY IN WATER ...: Nil
SPECIFIC GRAVITY: 0.896 at 60 Deg F (Water = 1)
BULK DENSITY: 7.46 Pounds per Gallon at 60 Deg F
PH: Not applicable
VISCOSITY: 100 cSt at 40 Deg C

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

POLYMERIZATION:

Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with strong oxidizing agents.

DECOMPOSITION:

In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

11. TOXICOLOGICAL INFORMATION

MISCELLANEOUS:

Routes of entry: Eyes, ingestion, inhalation, skin.

12. ECOLOGICAL INFORMATION

MISCELLANEOUS:

No data available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Altra Rock Drill 150 CP
D.O.T. SHIPPING NAME ...: Not Regulated by DOT

15. REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01 = CANADIAN DISCLOSURE LIST	02 = CERCLA Hazardous Substances
03 = TITLE V OF THE CLEAN AIR ACT	04 = SC Toxic Air Pollutants List
05 = SARA TITLE III - SECTION 313	06 = SARA Title III - Section 312
07 = CA PROPOSITION 65	08 = RCRA Hazardous Substances

No information available.

16. OTHER INFORMATION

REASON FOR ISSUE ...: NEW
APPROVAL DATE: July 10, 2009
SUPERCEDES DATE: New
RTN NUMBER: 00311450 (Official Copy)

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Allegheny Petroleum Products Co.. The data on this sheet are related only to the specific material designated herein. Allegheny Petroleum Products Co. assumes no legal responsibility for use or reliance upon these data.

END OF MSDS
