

(section 3 continued)

EYE:

May cause eye irritation.

SKIN:

May cause skin irritation. Prolonged or repeated contact may cause skin irritation, local redness and swelling.

INHALATION:

High vapor concentrations are irritating to the eyes, nose, throat, and lungs.

INGESTION:

May be harmful if swallowed.

CHRONIC EFFECTS:

None reported.

CARCINOGENICITY INFORMATION:

None known.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

SKIN CONTACT FIRST AID:

Wash skin with plenty of soap and water while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

INHALATION FIRST AID:

Remove to fresh air.

If not breathing, give artificial respiration and contact a physician immediately.

INGESTION FIRST AID:

For larger amounts, do NOT induce vomiting, but give one or two glasses of water to drink and get medical attention. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

COC Flash Point: 246.1 C (475.0 F)
Autoignition Temperature: > 315.6 C (> 600.1 F)

FLAMMABLE LIMITS IN AIR

LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:

Carbon dioxide, foam, or dry powder. Do not use water, because this product is oil based. Water may cause frothing.

FIRE & EXPLOSION HAZARDS:

Can burn in fire, releasing toxic vapors, fumes, and smoke.

FIRE FIGHTING INSTRUCTIONS:

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:

Hazardous decomposition products are oxides of carbon and nitrogen including CO and CO₂.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

INITIAL CONTAINMENT:

Absorb spills with inert material. Do not allow material to enter soil or surface water.

LARGE SPILLS PROCEDURE:

Absorb spill with inert material (e g, dry sand or earth), then place in a chemical waste container. Do not flush to sewer.

SMALL SPILLS PROCEDURE:

Absorb spills with inert material.

MISCELLANEOUS:

Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL) :

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS) :

Secure container after each use. Store in a cool dry area.

Avoid contact with strong oxidizing agents.

STORAGE PRECAUTIONS:

Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

EYE / FACE PROTECTION REQUIREMENTS:

When contact with the material may occur, chemical goggles and/or a face shield and protective clothing are recommended.

SKIN PROTECTION REQUIREMENTS:

Where contact is likely, wear chemical resistant gloves. Neoprene, polyvinyl chloride, butyl rubber, natural rubber and polyethylene are acceptable.

RESPIRATORY PROTECTION REQUIREMENTS:

Under normal use conditions, with adequate ventilation, no special handling equipment is required. If mists are produced, local ventilation may be required to keep exposure below limits.

EXPOSURE GUIDELINES:

RESIDUAL OILS, PETROLEUM, SOLVENT-DEWAXED

OSHA TWA: 5 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Thixotropic
COLOR: Amber
ODOR: Petroleum
BOILING POINT: 500 F
VAPOR PRESSURE: <0.02 mm Hg @ 300 F
VAPOR DENSITY: Heavier than air (Air = 1)
SOLUBILITY IN WATER ...: Nil
SPECIFIC GRAVITY: 0.86 @ 16 Deg C (Water = 1)
PH: Not applicable
% VOLATILES: nil %

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

POLYMERIZATION:

Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with strong oxidizing agents.

DECOMPOSITION:

In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

CONDITIONS TO AVOID:

Sources of ignition and temperatures above 50C (122F) - 60C (140F).

11. TOXICOLOGICAL INFORMATION

MISCELLANEOUS:

Routes of entry: Eyes, ingestion, inhalation, skin.

12. ECOLOGICAL INFORMATION

MISCELLANEOUS:

No data available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Altra Rugged Red LC EP1
D.O.T. SHIPPING NAME ...: Not Regulated by DOT

15. REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01 = CANADIAN DISCLOSURE LIST	02 = CERCLA Hazardous Substances
03 = TITLE V OF THE CLEAN AIR ACT	04 = SC Toxic Air Pollutants List
05 = SARA TITLE III - SECTION 313	06 = SARA Title III - Section 312
07 = CA PROPOSITION 65	08 = RCRA Hazardous Substances

No information available.

16. OTHER INFORMATION

REASON FOR ISSUE: NEW
APPROVAL DATE: July 2, 2007
SUPERCEDES DATE: New
RTN NUMBER: 00311077 (Official Copy)

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Allegheny Petroleum Products Co.. The data on this sheet are related only to the specific material designated herein. Allegheny Petroleum Products Co. assumes no legal responsibility for use or reliance upon these data.

END OF MSDS
