

Tricut 150S

SDS Number: 13208

Revision Date: 2/4/2015

Page 1 of 4

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Allegheny Petroleum Products Co.
999 Airbrake Avenue
Wilmerding, PA 15148

Phone: 1-412-829-1990

Product Name: Tricut 150S
Revision Date: 2/4/2015
SDS Number: 13208
CAS Number: Blend
Product Code: 13208
Synonyms: Metalworking fluid, Petroleum based lubricant

For emergencies contact Chemtrec at 1-800-424-9300

2

HAZARDS IDENTIFICATION

GHS Signal Word:
WARNING

GHS Hazard Pictograms:



GHS Classifications:
Health, Skin corrosion/irritation, 2

GHS Phrases:
H315 - Causes skin irritation

GHS Precautionary Statements:
P302+352 - IF ON SKIN: Wash with soap and water.

Tricut 150S

SDS Number: 13208

Revision Date: 2/4/2015

Page 2 of 4

3 COMPOSITION/INFORMATION ON INGREDIENTS**Ingredients:**

Chemical Name	Percentage	CAS#
Hydrotreated heavy naphthenic base oil	< 90	64741-52-5
Olefin sulfide	< 5	Proprietary
Non-hazardous additives	5.0 - 10.0	Proprietary

4 FIRST AID MEASURES

- Inhalation:** If symptoms develop, move victim to fresh air.
If symptoms persist, obtain medical attention.
- Skin Contact:** Wash with soap and water.
Remove contaminated clothing and wash before reuse.
Get medical attention if needed.
- Eye Contact:** Flush with water for several minutes.
If effects occur, consult a physician.
- Ingestion:** Rinse mouth with water.
If symptoms develop, obtain medical attention.

5 FIRE FIGHTING MEASURES

- Flash Point:** 180 C (356 F)
Flash Point Method: 315.6 C (600.1 F)

Use dry powder, foam, or carbon dioxide fire extinguishers.
Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

6 ACCIDENTAL RELEASE MEASURES

Contain spilled material.
Collect in suitable and properly labeled containers.
Pick up excess with inert absorbant material
Keep away from drains and ground water.

Tricut 150S

SDS Number: 13208

Revision Date: 2/4/2015

Page 3 of 4

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing.
Keep away from sources of ignition.
Handle with care and avoid spillage on the floor (slippage).

Storage Requirements: Keep away from sources of ignition.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equip: Use of safety glasses and gloves are recommended.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber

Physical State: Liquid

Solubility: Nil

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.

Conditions to Avoid: High temperatures and open flame.

11 TOXICOLOGICAL INFORMATION

Repeated skin contact with this product may cause dermatitis or an oil acne.

No test data available on product.

No component is listed as a carcinogen, mutagen, or teratogen.

LD50 / LC50 - No data available

12 ECOLOGICAL INFORMATION

Avoid exposing to the environment, no specific aquatic data available

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

Do not flush to surface water or drains

Tricut 150S

SDS Number: 13208

Revision Date: 2/4/2015

Page 4 of 4

14 **TRANSPORT INFORMATION**

Not regulated by DOT

15 **REGULATORY INFORMATION**

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16 **OTHER INFORMATION**

The information contained in this Safety Data Sheet relates only to the specific material designated. Allegheny Petroleum Products Co. assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Allegheny Petroleum Products Co.