



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Altra Rock Drill Oil 46
Synonyms: Petroleum based lubricant
Chemical Name: Hydrotreated heavy paraffinic distillate
Chemical Family: Petroleum Distillate
CAS Number: Blend

Company Identification

Allegheny Petroleum Products Co.
999 Airbrake Avenue
Wilmerding, PA 15148 USA
1-412-829-1990 (For product information)
1-800-424-9300 (For emergencies)
1-800-424-9300 or 1-703-527-3887 (CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

<u>Chemical Name</u>	<u>Amount</u>	<u>CAS Number</u>
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	> 90.0 %	64742-65-0
ADDITIVES	< 10.0 %	Mixture

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

3. HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW *****
*
* Not expected to cause a severe emergency hazard. *

*

HMIS Rating - Health: 1
 Flammability: 1
 Reactivity: 0

NFPA Rating - Health: 1
 Flammability: 1
 Reactivity: 0
 Special Hazard: N/A

POTENTIAL HEALTH EFFECTS

EYE:

Contact may cause eye irritation and redness.

SKIN:

Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION:

Inhalation of vapors or mist may be mildly irritating to the nose, throat, and respiratory tract.

INGESTION:

Small amounts swallowed during normal handling operations are not likely to cause injury.

CHRONIC EFFECTS:

No adverse effects have been documented in humans as a result of chronic exposure.

CARCINOGENICITY INFORMATION:

Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:

Flush eye with water for 15 minutes.

Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:

Wash skin with soap and water.

Thoroughly wash (or discard) clothing and shoes before reuse.

(section 4 continued)

INHALATION FIRST AID:

Remove to fresh air.

If not breathing, give artificial respiration.

INGESTION FIRST AID:

If vomiting should occur spontaneously, keep airway clear.

NOTES TO PHYSICIAN:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

COC Flash Point: 212.8 C (415.0 F)

Autoignition Temperature: N/A

FLAMMABLE LIMITS IN AIR

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA:

Carbon dioxide, foam, or dry powder. Water may be used to cool below flash point.

FIRE FIGHTING INSTRUCTIONS:

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:

Fumes, smoke and carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Wear appropriate personal protective equipment.

INITIAL CONTAINMENT:

Absorb spills with inert material.

LARGE SPILLS PROCEDURE:

Contain spilled material.

Large spillage should be dammed-off and pumped into containers.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

(section 6 continued)

SMALL SPILLS PROCEDURE:

Clean up area by absorbent material.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Store in a cool dry area.

Keep container closed to avoid contamination.

STORAGE PRECAUTIONS:

Keep container closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical ventilation to maintain exposure below PEL/TLV (s).

EYE / FACE PROTECTION REQUIREMENTS:

Where contact with this material is likely, eye protection is recommended.

SKIN PROTECTION REQUIREMENTS:

When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

EXPOSURE GUIDELINES:

No Information Available.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Amber
ODOR: Typical Petroleum
BOILING POINT: N/A F
VAPOR PRESSURE: Nil mm Hg
VAPOR DENSITY: >1 (Air = 1)
SOLUBILITY IN WATER: Nil
SPECIFIC GRAVITY: 0.87 (Water = 1)
MELTING/FREEZING POINT: N/A F
VISCOSITY: 46 cSt at 40 Deg C
VOLATILE ORGANIC COMPOUNDS (VOC): Nil

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

POLYMERIZATION:

Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with strong oxidizing agents.

DECOMPOSITION:

In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

CONDITIONS TO AVOID:

Sources of ignition.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS:

Minimal irritation on contact.

SKIN EFFECTS:

Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

ACUTE ORAL EFFECTS:

Tests on similar materials indicate low order of acute oral toxicity.

ACUTE INHALATION EFFECTS:

Low acute toxicity expected on inhalation.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:

Ecotoxicological Information: No specific aquatic data available for this product.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Do not flush to surface water or sanitary sewer system.

CONTAINER DISPOSAL:

Empty drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner.

All other containers should be disposed of in an environmentally safe manner.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Altra Rock Drill Oil 46
D.O.T. SHIPPING NAME: Not regulated by DOT
TECHNICAL SHIPPING NAME ...: Petroleum Oil, Not Regulated

15. REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01 = CANADIAN DISCLOSURE LIST	02 = SARA Title III - Section 313
03 = CERCLA HAZARDOUS SUBSTANCES	04 = Clean Air Act - Section 112
05 = TITLE V	06 = CA Proposition 65
07 = SC TOXIC AIR POLLUTANTS LIST	

MISCELLANEOUS INFORMATION:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

16. OTHER INFORMATION

REASON FOR ISSUE ...: Revised
APPROVAL DATE: May 28, 2004
SUPERCEDES DATE: New
RTN NUMBER: 00310534 (Official Copy)

(section 16 continued)

ADDITIONAL INFORMATION:

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Allegheny Petroleum Products Co.. The data on this sheet are related only to the specific material designated herein. Allegheny Petroleum Products Co. assumes no legal responsibility for use or reliance upon these data.

END OF MSDS
