



Dezol SAE 20W-50 Engine Oil

Dyna-Plex 21C® Dezol SAE 20W-50 Engine Oil provides optimum protection against deposits while controlling high temperature varnish. Its excellent film strength provides a reduction in engine wear that occurs in heavily loaded duty service engines.

Dyna-Plex 21C Dezol SAE 20W-50 Engine Oil contains anti-wear additives, which provides outstanding protection against scuffing of highly loaded cams, hydraulic lifters and other valve train components, resulting in reduced engine wear. In addition, oxidation inhibitors provide “oil thickening” resistance and rust inhibitors protect against rusting and corrosion of valve lifters, bearings, cylinder walls and other critical engine parts. Because of the shear stable viscosity modifier, Dyna-Plex 21C Dezol SAE 20W-50 Engine Oil reduces engine oil shear allowing it to remain in viscosity grade.

<u>PROPERTY</u>	<u>SAE 20W-50</u>
Gravity, °API	27.0
Lbs./gallon	7.44
Viscosity @ 40°C, cSt	175
Viscosity @ 100°C, cSt	18.5
Viscosity Index	120
Pour Point, °C	-24
Flash Point, °C	225

Meets or exceeds the following tests and requirements:
API Service Classification CF, CF-2 and SJ